

TYPOSZEREG STOWER ST-S



S-TOWER
WIEŻE TELEKOMUNIKACYJNE

SEGMENT				ST-30S	ST-36S	ST-42S	ST-48S	ST-54S	ST-60S	
PROFIL KRAWĘŻNIKA [mm]	WYSOKOŚĆ [m]	SZEROKOŚĆ [mm]	OZN.							
Ø88,9	6,0	1500/1500	S-1							
Ø101,6		1500/2000	S-2							
Ø114,3		2000/2500	S-3							
Ø114,3		2500/3000	S-4							
Ø139,7		3000/3500	S-5							
Ø168,3		3500/4000	S-6							
Ø168,3		4000/4500	S-7							
Ø168,3		4500/5000	S-8							
Ø193,7		5000/5500	S-9							
Ø193,7		5500/6000	S-10							
Ø193,7		6000/6500	S-11							
WYSOKOŚĆ CAŁKOWITA [m]				30,0	36,0	42,0	48,0	54,0	60,0	
PRZEKRÓJ TRZONU				Trójkąt						
MASA [kg] (trzon, drabina, łączniki)				5674,0	6463,0	7235,0	7891,0	8452,0	8947,0	
NOŚNOŚĆ (Ax Cf) [m2] <small>Nośność w 1 i 3 strefie wiatrowej do wys. 300 m n.p.m.</small>				37,1	35,0	31,0	28,9	27,0	24,8	